



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION I

5 POST OFFICE SQUARE, SUITE 100
BOSTON, MASSACHUSETTS 02109-3912**CERTIFIED MAIL - RETURN RECEIPT REQUESTED**

JUN 15 2011

Mr. George Estrada
Vice President for Facilities
The University of Bridgeport
126 Park Avenue
Bridgeport, Connecticut 06604

Re: PCB Cleanup and Disposal Approval under §761.61(a)
Barnum Hall
The University of Bridgeport
Bridgeport, Connecticut

Dear Mr. Estrada:

This is in response to the University of Bridgeport (the University) Notification¹ to address PCB-contaminated concrete and soils in an underground vault located adjacent to Barnum Hall, Bridgeport, Connecticut (the Site). The Site contains PCB concentrations that exceed the allowable PCB levels for unrestricted use under the federal PCB regulations at 40 CFR § 761.61(a). The University has requested an approval to clean up and dispose of the PCB-contaminated concrete and soils located at the Site under the PCB self-implementing cleanup and disposal option (SIP) at 40 CFR § 761.61(a).

The University has determined that the Site meets the definition for a *high occupancy area* under § 761.3 which would allow less than or equal to (\leq) 1 part per million (ppm) PCBs to remain on-site without further restriction.

The University is proposing the following PCB cleanup and disposal activities under § 761.61(a):

- Remove all PCB-contaminated concrete and soils at greater than ($>$) 1 ppm;
- Conduct verification sampling to insure that the concrete common wall and soils meet the \leq 1 ppm cleanup standard; and,

¹ Information was submitted on behalf of the University of Bridgeport by HRP Associates, Inc. The information was provided to satisfy the notification requirement under 40 CFR § 761.61(a)(3). Information was provided dated May 6, 2011 (SIP and Contractor work plan), June 6, 2011 (Response to Comments), June 7, 2011 (Laboratory Certification), June 8, 2011 (Revised Contractor work plan), and June 9, 2011 (e-mail response to comments). These submittals will be referred to as the "Notification."

- Dispose of concrete and soils with PCB concentrations > 1 ppm but less than (<) 50 ppm at a state permitted disposal facility in accordance with § 761.61(a)(5)(i)(B)(2)(ii);

The University's Notification meets the requirements at § 761.61(a)(3). The University may proceed with its PCB cleanup and disposal under 40 CFR § 761.61(a); its Notification; and this Approval, subject to the conditions of Attachment 1.

This Approval does not release the University from any applicable requirements of federal, state or local law, including the requirements related to cleanup and disposal of PCB-contaminated wastes under the Connecticut Department of Environmental Protection (CTDEP) regulations.


This Approval only addresses cleanup and disposal of the *PCB remediation waste* identified in the Notification. In the event that the University identifies other PCB-contaminated wastes subject to cleanup and disposal under the PCB regulations, the University will be required to notify EPA and cleanup the PCB-contaminated wastes in accordance with 40 CFR Part 761 (see Approval Condition 1.)

Questions and correspondence regarding this Approval should be directed to:

Katherine A. Woodward, PE, Project Manager
United States Environmental Protection Agency
5 Post Office Square, Suite 100
Mail Code: OSRR07-2
Boston, Massachusetts 02109-3912
Telephone: (617) 918-1353
Facsimile: (617) 918-0527

EPA shall not consider this project complete until it has received all submittals required under this Approval. Please be aware that upon EPA receipt and review of the submittals, EPA may request any additional information necessary to establish that the work has been completed in accordance with 40 CFR Part 761, the Notification, and this Approval.

Sincerely,



Mary Sanderson, Chief
Remediation & Restoration II Branch

Attachment 1-PCB Approval Conditions

Attachment 2-Region 1 Standard Operating Procedure for Sampling Porous Surfaces for Polychlorinated Biphenyls (PCBs)-Revision 4 dated May 5, 2011
(See Condition 12)

cc: Eric Boswell, HRP Associates, Inc
Gary Trombly, CTDEP
File

ATTACHMENT 1:

**PCB CLEANUP AND DISPOSAL APPROVAL CONDITIONS
BARNUM HALL
THE UNIVERSITY OF BRIDGEPORT
BRIDGEPORT, CONNECTICUT**

GENERAL CONDITIONS

1. This Approval is granted under the authority of Section 6(e) of the Toxic Substances Control Act (TSCA), 15 U.S.C. § 2605(e), and the PCB regulations at 40 CFR Part 761, and applies solely to *PCB remediation waste* located at the Site as identified in the Notification.
 - a. In the event that the University of Bridgeport (the University) identifies other PCB-contaminated wastes subject to cleanup and disposal under the PCB regulations, the University will be required to notify EPA and clean up the PCB-contaminated wastes in accordance with 40 CFR Part 761.
 - b. The University may submit a separate plan to address the PCB contamination or may modify the Notification to incorporate cleanup of the PCBs under this Approval in accordance with Condition 15.
2. The University shall conduct on-site activities in accordance with the conditions of this Approval and with the Notification.
3. In the event that the cleanup plan described in the Notification differs from the conditions specified in this Approval, the conditions of this Approval shall govern.
4. The terms and abbreviations used herein shall have the meanings as defined in 40 CFR § 761.3 unless otherwise defined within this Approval.
5. The University must comply with all applicable federal, state and local regulations in the storage, handling, and disposal of all PCB wastes, including PCBs, PCB Items and decontamination wastes generated under this Approval. In the event of a new spill during response actions, the University shall contact EPA within 24 hours for direction on sampling and cleanup requirements.
6. The University is responsible for the actions of all officers, employees, agents, contractors, subcontractors, and others who are involved in activities conducted under this Approval. If at any time the University has or receives information indicating that the University or any other person has failed, or may have failed, to comply with any provision of this Approval, it must report the information to EPA in writing within 24 hours of having or receiving the information.

7. This Approval does not constitute a determination by EPA that the transporters or disposal facilities selected by the University are authorized to conduct the activities set forth in the Notification. The University is responsible for ensuring that its selected transporters and disposal facilities are authorized to conduct these activities in accordance with all applicable federal, state and local statutes and regulations.
8. This Approval does not: 1) waive or compromise EPA's enforcement and regulatory authority; 2) release the University from compliance with any applicable requirements of federal, state or local law; or 3) release the University from liability for, or otherwise resolve any violations of federal, state or local law.

NOTIFICATION AND CERTIFICATION CONDITIONS

9. This Approval may be revoked if the EPA does not receive written notification from the University of its acceptance of the conditions of this Approval within 10 business days of receipt.
10. Within 5 days of initiating onsite work under this Approval, the University shall submit a certification signed by its selected remediation contractor, stating that the contractor has read and understands the Notification, and agrees to abide by the conditions specified in this Approval.

REMEDIAL AND DISPOSAL CONDITIONS

11. The cleanup level for bulk *PCB remediation waste* (i.e., concrete and soils) at the Site shall be in accordance with 40 CFR § 761.61(a)(4).
 - a. Bulk *PCB remediation waste* (i.e. soil) samples shall be collected on a bulk basis (e.g. mg/Kg) and reported on a dry-weight basis. Verification sampling shall comply with Subpart O; samples shall be collected from both excavation bottoms and sidewalls, as applicable.
 - b. All post-cleanup verification sampling for *porous surfaces* (i.e. concrete) shall be performed on a bulk basis (i.e. mg/kg). Verification sampling for *porous surfaces* shall be conducted in accordance with the EPA Region 1 Standard Operating Procedure For Sampling Porous Surfaces for Polychlorinated Biphenyls (PCBs) Revision 4, dated May 5, 2011, at a maximum depth interval of 0.5 inches, and in accordance with the frequency requirements at Subpart O.
 - c. Bulk *PCB remediation waste* with greater than (>) 1ppm but less than (<) 50 ppm shall be disposed of in accordance with § 761.61(a)(5)(i)(B)(2)(ii) or § 761.61(a)(5)(i)(B)(2)(iii).

- d. Chemical extraction for PCBs shall be conducted using Methods 3500B/3540C of SW-846 for solid matrices and Method 3500B/3510C of SW-846 for aqueous matrices; and, chemical analysis for PCBs shall be conducted using Method 8082 of SW-846, unless another extraction or analytical method(s) is validated according to Subpart Q.
13. All PCB waste (regardless of concentration) generated as a result of the activities described in the Notification, excluding any decontaminated materials, shall be marked in accordance with § 761.40; stored in a manner prescribed in § 761.65; and, disposed of in accordance with 40 CFR § 761.61(a)(5), unless otherwise specified below:
- a. Decontamination wastes and residues shall be disposed of in accordance with 40 CFR § 761.79(g).
 - b. Moveable equipment, tools, and sampling equipment shall be decontaminated in accordance with either 40 CFR § 761.79(b)(3)(i)(A), § 761.79(b)(3)(ii)(A), or § 761.79(c)(2).
 - c. PCB-contaminated water generated during decontamination or dewatering shall be decontaminated in accordance with 40 CFR § 761.79(b)(1) or disposed of under § 761.60.

INSPECTION, MODIFICATION AND REVOCATION CONDITIONS

14. The University shall allow any authorized representative of the Administrator of the EPA to inspect the Site, to inspect records, and to take samples as may be necessary to determine compliance with the PCB regulations and this Approval. Any refusal by the University to allow such an inspection (as authorized by Section 11 of TSCA) shall be grounds for revocation of this Approval.
15. Any proposed modification(s) in the plan, specifications, or information in the Notification must be submitted to EPA no less than 14 calendar days prior to the proposed implementation of the change. Such proposed modifications will be subject to the procedures of 40 CFR § 761.61(a)(3)(ii).
16. Any departure from the conditions of this Approval without prior, written authorization from the EPA may result in the revocation, suspension and/or modification of the Approval, in addition to any other legal or equitable relief or remedy the EPA may choose to pursue.

17. Any misrepresentation or omission of any material fact in the Notification or in any records or reports may result in the EPA's revocation, suspension and/or modification of the Approval, in addition to any other legal or equitable relief or remedy the EPA may choose to pursue.
18. Approval for these activities may be revoked, modified or otherwise altered: if EPA finds a violation of the conditions of this Approval or of 40 CFR Part 761, including EPA's PCB Spill Cleanup Policy, or other applicable rules and regulations; or, if EPA finds that these activities present an unreasonable risk to public health or the environment.

RECORDKEEPING AND REPORTING CONDITIONS

19. The University shall prepare and maintain all records and documents required by 40 CFR Part 761, including but not limited to the records required under Subparts J and K. A written record of the cleanup and the analytical sampling shall be established and maintained by the University in one centralized location until such time as EPA authorizes, in writing, an alternative disposition for such records. All records shall be made available for inspection by authorized representatives of EPA.
20. The University shall submit a final report to EPA within 60 days of completion of the activities authorized under this Approval. At a minimum, this final report shall include: a short narrative of the cleanup and disposal activities; characterization and confirmation sampling analytical results (as applicable); copies of the accompanying analytical chains of custody; field and laboratory quality control/quality assurance checks; an estimate of the quantity of PCB waste disposed of and the size of the remediated area(s); copies of manifests and/or bills of lading; and copies of certificates of disposal or similar certifications issued by the disposer.
21. Required submittals shall be mailed to:

Katherine A Woodward, PE, Project Manager
United States Environmental Protection Agency
5 Post Office Square, Suite 100
Mail Code: OSRR07-2
Boston, Massachusetts 02109-3912
22. No record, report or communication required under this Approval shall qualify as a self-audit or voluntary disclosure under EPA audit, self disclosure or penalty policies.

END OF ATTACHMENT 1


**STANDARD OPERATING PROCEDURE
FOR SAMPLING POROUS SURFACES
FOR POLYCHLORINATED BIPHENYLS (PCBs)**

The Office of Environmental Measurement and Evaluation

EPA New England – Region 1

11 Technology Dr.


North Chelmsford, MA 01863

Prepared by: 
Dan Granz, Environmental Engineer


5/5/11
Date

Reviewed by: 
Kim Tisa, TSCA PCB Coordinator

5/5/11
Date

Reviewed by: 
Jerry Keefe – EIA Team Leader

05/23/11
Date

Approved by: 
Dan Boudreau, EIA Chemistry Team Leader

5/23/11
Date

Disclaimer: The controlled version of this document is the electronic version viewed on-line only. If this is a printed copy of the document, it is an uncontrolled version and may or may not be the version.

This document contains direction developed solely to provide internal guidance to U.S. Environmental Protection Agency (EPA) personnel. EPA retains the discretion to adopt approaches that differ from these procedures on a case by case basis. The procedures set forth do not create any rights, substantive or procedural, enforceable at law by a party to litigation with EPA or the United States.

Table of Contents

1.0	Scope and Application	4
2.0	Summary of Method	4
3.0	Definitions.....	4
4.0	Health and Safety Warnings.....	5
5.0	Interferences.....	6
6.0	Personnel Qualifications	6
7.0	Equipment and Supplies	6
8.0	Sampling Design.....	7
9.0	Sample Collection.....	7
10.0	Sample Handling, Preservation, and Storage.....	10
11.0	Decontamination	11
12.0	Data and Record Management.....	11
13.0	Quality Control and Quality Assurance.....	11
14.0	Waste Management and Pollution Prevention.....	12
15.0	References.....	12

Attachments:

Example of Custody Seal and Sample Label

Example of Chain of Custody Form

1.0 Scope and Application

- 1.1 This Standard Operating Procedure (SOP) is suitable for collection of a porous matrix sample for analysis of Polychlorinated Biphenyls (PCBs).
- 1.2 This SOP describes sampling techniques for both hard and soft porous surfaces.
 - 1.2.1 Hard surfaces, and most soft surfaces, can be sampled using an impact hammer drill to generate a uniform, finely ground, powder to be extracted and analyzed for PCBs. This procedure is primarily geared at providing enough sample quantity for two analyses. Hard porous surfaces include concrete, brick, asphalt, cement, sandstone, limestone, unglazed ceramics, and other possible PCB suspected material. This procedure may also be used on other softer porous surfaces, such as wood.
 - 1.2.2 Soft surfaces can be sampled using a chisel or sharp knife to generate a representative sample to be extracted and analyzed for PCBs. Soft porous surfaces include wood, wall plasterboard, low density plastics, rubber, caulking, and other PCB suspected material.
- 1.3 This SOP provides for collection of surface samples (0 – 0.5 inches) and delineation of PCB contamination throughout the core of the porous surface. The procedure can be used to sample the porous surface at distinctly different depth zones.

2.0 Method Summary

A one-inch or other sized diameter carbide drill bit is used in a rotary impact hammer drill to generate a fine powder, or other representative sample, suitable for extraction and analysis of PCBs from porous surfaces. This method also allows the use of chisels or knives for the collection of samples from soft porous surfaces for PCB analysis.

3.0 Definitions

- 3.1 Field/Bottle Blank: A sample container of the same lot as the containers used for the environmental samples. This evaluates PCB contamination introduced from the sample container(s) from a common lot.
- 3.2 Equipment/Rinse/Rinsate Blanks: A sample that is collected by pouring hexane over the sample collection equipment after decontamination and before sample collection. The sample is collected in the appropriate sample container identical to the sample containers. This represents background contamination resulting from the field equipment, sampling procedure, sample container, and shipment.

- 3.3 Field Replicates/Duplicates: Two or more samples collected at the same sampling location. Field replicates should be samples collected side by side. Field replicates represent the precision of the whole method, site heterogeneity, field sampling, and the laboratory analysis.
- 3.4 Field Split Samples: Two or more representative subsamples taken from one environmental sample in the field. Prior to splitting, the environmental sample is homogenized to correct for sample heterogeneity that would adversely impact data comparability. Field split samples are usually analyzed by different laboratories (interlaboratory comparison) or by the same laboratory (intralaboratory comparison). Field splits are used to assess sample handling procedures from field to laboratory and laboratory comparability.
- 3.5 Laboratory Quality Samples: Additional samples that will be collected for the laboratory's quality control program: matrix spike, matrix spike duplicate, laboratory duplicates, etc.
- 3.6 Proficiency Testing (PT)/Performance Evaluation (PE) Sample: A sample, the composition of which is unknown to the laboratory or analyst, provided to the analyst or laboratory to assess the capability to produce results within acceptable criteria. This is optional depending on the data quality objectives. If possible, it is recommended that the PE sample be of similar matrix as the porous surface(s) being sampled.
- 3.7 Porous Surface: Any surface that allows PCBs to penetrate or pass into itself including, but not limited to, paint or coating on metal; corroded metal; fibrous glass or glass wool; unglazed ceramics; ceramics with porous glaze; porous building stone such as sandstone, travertine, limestone, or coral rock; low density plastics such as Styrofoam and low density polyethylene; coated (varnished or painted) or uncoated wood; painted or unpainted concrete or cement; plaster; plasterboard; wallboard; rubber; caulking; fiberboard; chipboard; asphalt; or tar paper.
- 3.8 Shipping Container Temperature Blank: A water sample that is transported to the laboratory to measure the temperature of the samples in the cooler.
- 4.0 **Health and Safety**
- 4.1 Eye, respiratory, and hearing protection are required at all times during sample drilling. A properly fitted respirator is required for hard porous surface sampling. A respirator is recommended whenever there is a risk of inhalation of either particulate or volatilized PCBs during sampling.
- 4.2 All proper personal protection clothing and equipment must be worn.

4.3 When working with potentially hazardous materials or situations, follow EPA, OSHA, and specific health or safety procedures.

4.4 Care must be exercised when using an electrical drill and sharp cutting objects.

5.0 Interferences and Potential Problems

5.1 This sampling technique produces a finely ground uniform powder, which minimizes the physical matrix effects from variations in the sample consistency (i.e., particle size, uniformity, homogeneity, and surface condition). Matrix spike analysis of a sample is highly recommended to monitor for any matrix related interferences.

5.2 Nitrile gloves are recommended. Latex gloves must not be used due to possible phthalate contamination.

5.3 Interferences may result from using contaminated equipment, solvents, reagents, sample containers, or sampling in a disturbed area. The drill bit must be decontaminated between samples. (see Section 11.0.)

5.4 Cross contamination problems can be eliminated or minimized through the use of dedicated sampling equipment.

6.0 Personnel Qualifications

6.1 All field samplers working at hazardous materials/waste sites are required to take a 40 hour health and safety training course prior to engaging in any field activities. Subsequently, an 8 hour refresher health and safety course is required annually.

6.2 The field sampler should be trained by an experienced sampler before initiating this procedure.

6.3 All personnel shall be responsible for complying with all quality assurance/quality control requirements that pertain to their organizational/technical function.

7.0 Equipment and Supplies

7.1 This list varies with the matrix and if depth profiling is required

- Rotary impact hammer variable speed drill
- 1-inch or other suitable (1/2, 3/4, etc.) diameter carbide tip drill bits
- Steel chisel or sharp cutting knife, and hammer
- Brush and cloths to clean area
- Stainless steel scoopulas

Aluminum foil to collect the powder sample
1 quart Cubitainer with the top cut out to collect the powder sample
Aluminum weighing pans to collect the powder sample
Cleaned glass container (2 oz or 40 mL) with Teflon lined cap
Decontamination supplies: hexane, two small buckets, a scrub brush, detergent, deionized water, hexane squirt bottle, and paper towels
Dedicated vacuum cleaner with a disposable filter or a vacuum pump with a dust filter
Polyethylene tubing and Pasteur pipettes
Sample tags/labels, custody seals, and Chain-of-Custody form

8.0 Sampling Design

8.1 A sufficient number of samples must be collected to meet the data quality objectives of the project. If the source of the PCB contamination is regulated under the federal TSCA PCB Regulations at 40 CFR Part 761, the sampler should insure that the sampling design is sufficient to meet any investigation or verification sampling requirements. At a minimum, the following is recommended:

- 8.1.1 Suspected stained area (s) should be sampled.
- 8.1.2 At each separate location, collect at least 3 samples of each type of porous surface, regardless of the amount of each type of porous surface present.
- 8.1.3 In areas where PCB equipment was used or where PCBs were stored, samples should be collected at a frequency of 1 sample/100 square feet (ft²).

9.0 Sample Collection

9.1 Hard Porous Surfaces

- 9.1.1 Lock a 1-inch or another size diameter carbide drill bit into the impact hammer drill and plug the drill into an appropriate power source. For easy identification, sample locations may be pre-marked using a marker or paint. (Note: the actual drilling point must not be marked.) Remove any debris with a clean brush or cloth prior to drilling. All sampling decisions of this nature should be noted in the sampling logbook.
- 9.1.2 Use a Cubitainer with the top cut off or aluminum foil to contain the powdered sample. Begin drilling in the designated location. Apply steady even pressure and let the drill do the work. Applying too much pressure will generate excessive heat and dull the drill bit prematurely. The drill will provide a finely ground powder that can be easily collected.

9.1.3 Samples should be collected at ½-inch depth intervals. Thus, the initial surface sample should be collected from 0 – 0.5 inches. A ½-inch deep hole generates about 10 grams (20 mL) of powder. Multiple holes located closely adjacent to each other, may be needed to generate sufficient sample volumes for a PCB determination. It is strongly recommended that the analytical laboratory be consulted on the minimum sample size needed for PCB extraction and analysis.

9.1.4 Wall and Ceiling Sampling: A team of two samplers will be required for wall and ceiling sampling. The second person will hold a clean catch surface (e.g. an aluminum pan) below the drill to collect the falling powder. Alternatively, use the chuck-end of the drill bit and punch a hole through the center of the collection pan. The drill bit is then mounted through the pan and into the drill. For ceilings, the drill may be held at an angle to collect the powder. Thus the driller can be drilling at an angle while the assistant steadies the pan to catch the falling powder. As a precaution, it may be advantageous to tape a piece of plastic around the drill, just below the chuck, to avoid dust contaminating the body of the drill and entering the drill's cooling vents. Caution must be taken to prevent obstruction of the drill's cooling vents.

9.2 Soft Porous Surfaces

9.2.1 The procedure for the hard porous surface may be used for certain soft porous surfaces, such as wood.

9.2.2 Samples should be collected at no more than ½-inch depth intervals using a metal chisel or sharp cutting knife. Thus, the initial surface sample should be collected from 0 – 0.5 inches. It is important to collect at least 10 grams for analysis.

9.2.3 For soft porous surfaces, such as caulking and rubber, a representative sample can be collected using a metal chisel or sharp cutting knife.

9.3 Multiple Depth Sampling

9.3.1 Multiple Depth Sampling may not be applicable to certain porous surfaces, such as caulking.

9.3.2 Collect the surface sample as outlined in Section 9.1 or 9.2.

9.3.3 Use the vacuum pump or cleaner to clean out the hole.

9.3.4 To collect multiple depths there are two options.


9.3.4.1 Option one: drill sequentially ½-inch increments with the 1 inch drill.

9.3.4.2 Option two: drill with the 1 inch bit and either make the hole larger or use a smaller bit to take the next ½- inch sample.

9.3.5 A stainless steel scoopula will make it easier to collect the sample from the bottom of the hole.

9.4 Vacuum Trap Design and Clean-out

The trap presented in Figure 1 is a convenient and thorough way for collecting and removing concrete powder from drilled holes. The trap system is designed to allow for control of the suction from the vacuum pump and easy trap clean-out between samples. Note, by placing a hole in the inlet tube (see Figure 1), a finger on the hand holding the trap can be used to control the suction at the sampling tip. Thus, when this hole is left completely open, there will be no suction, and the sampler can have complete control over where and what to sample. To change-out between samples the following steps should be taken: 1) the Pasteur pipette and piece of polyethylene tubing at the sample inlet should be replaced with new materials, 2) the portion of the rubber stopper and glass tubing that was in the trap should be wiped down with a clean damp paper towel (wetted with deionized water) and then dried with a fresh paper towel, 3) a clean pipe cleaner should be drawn through the glass inlet tube to remove any concrete dust present, and 4) the glass tube or flask used to collect the sample should be swapped out with a clean decontaminated sample trap. Having several clean tubes or flasks on hand will facilitate change-out between samples.

Figure 1

Note: the holes should be vacuumed thoroughly to minimize any cross-contamination between sample depths and the bits should be decontaminated between samples. (See Section 11.0)

10.0 Sample Handling, Preservation, and Storage

- 10.1 Samples must be collected in glass containers for PCB analyses. In general, a 2-ounce sample container with a Teflon-lined cap (wide-mouth jars are preferred) will hold sufficient mass for most analyses. A 2-ounce jar can hold roughly 90 grams of sample.
- 10.2 Samples are to be shipped refrigerated and maintained at $\leq 6^{\circ}\text{C}$ until the time of extraction and analysis.
- 10.3 The suggested holding time for PCB samples is 14 days to extraction.

11.0 Decontamination

- 11.1 Assemble two decontamination buckets. The first bucket contains a detergent and potable water solution, and the second bucket is for rinsate. Place all used drill bits, hose for the vacuum cleaner, and utensils in the detergent and water bucket. Scrub each piece thoroughly using the scrub brush. Note, the powder does cling to the metal surfaces, so care should be taken during this step, especially with the twists and curves of the drill bits. Next, rinse each piece with water and hexane. Place the rinsed pieces on clean paper towels and individually dry and inspect each piece. Note: all pieces should be dry prior to reuse.
- 11.2 Lightly contaminated drill bits and utensils may be wiped with a hexane soaked cloth and hexane rinsed for decontamination.

12.0 Data and Record Management

- 12.1 All data and information collection should follow a Field Data Management SOP or Quality Assurance Project Plan (QAPP).
- 12.2 Follow the chain of custody procedures to release the samples to the laboratory. A copy is kept with the sampling records.
- 12.3 The field data is stored for at least 3 years.

13.0 Quality Control and Quality Assurance

- 13.1 Representative samples are required. The sampler will evaluate the site specific conditions to assure the sample will be representative.
- 13.2 All sampling equipment must be decontaminated prior to use and between each discrete sample.
- 13.3 All field Quality Control (QC) sample requirements in a Sample and Analysis Plan (SAP) or QAPP must be followed. The SAP or QAPP may involve field blanks, equipment blanks, field duplicates and/or the collection of extra samples for the laboratory's quality control program.
- 13.4 Field duplicates should be collected at a minimum frequency of 1 per 20 samples or 1 per non-related porous matrix, whichever is greater.

14.0 Waste Management and Pollution Prevention


- 14.1 During field sampling events there may be PCB and/or hazardous waste produced from the sample collection. The waste must be handled and disposed of in accordance with federal, state, and local regulations. The dust filter, and tubing if a vacuum pump is used, is disposed after each site investigation. This waste will be treated as PCB waste if the samples are positive for PCBs. It may be possible to manage or dispose of the waste produced at the site where the work was performed. If the site does not meet regulatory requirements for these types of activities, the waste must be transported to a facility permitted to manage and/or dispose of the waste.


15.0 References

1. Guidance for the Preparation of Standard Operating Procedures for Quality-Related Operations, QA/G-6, EPA/600/R-96/027, November 1995.
2. 40 CFR Part 761 – Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution In Commerce, and Use Prohibitions
3. Sample Container and Holding Time: RCRA SW 846, Chapter 4, Table 4.1, Revision 4, February, 2007.

Example of Sample Label and Custody Seal

U.S. ENVIRONMENTAL PROTECTION AGENCY -- REGION I BOSTON, MASS.	
LABEL	NAME OF UNIT AND ADDRESS ENVIRONMENTAL SERVICES DIVISION 60 WESTVIEW STREET LEXINGTON, MASSACHUSETTS 02173
	DATE: YR/MO/DAY TIME STATION NO.
SAMPLE	SOURCE OF SAMPLE SAMPLING CREW (FIRST, INITIAL, LAST NAME)
	SAMPLE NO. SUB NO. PRESERVATIVE
	AMOUNT ANALYSIS

 UNITED STATES ENVIRONMENTAL PROTECTION AGENCY OFFICIAL SAMPLE SEAL	SAMPLE NO.	DATE	SEAL BROKEN BY DATE	EPA FORM 7500-2 (11-75)
	SIGNATURE			
	PRINT NAME AND TITLE (Inspector, Analyst or Technician)			



REGION 1

CHAIN OF CUSTODY RECORD

[illegible]

Distribution: Original Accompanies Shipment: Copy to Coordinator Field File

☆ U.S. GOVERNMENT PRINTING OFFICE: 2004-700-078

1-16940